



Winterizing Your Beachcomber Hot Tub

- 1 Start by draining your hot tub (refer to page 28 of your Owner's Guide). Then, remove jet pump #1 return assemblies from the pump to the hot tub wall. If your hot tub is a LEEP model, undo the pump to heater plumbing assembly at the pump and heater and remove.
- 2 With a ShopVac on blow, hold the hose up against the fitting on the hot tub wall or at the heater and blow out all jets running off pump #1.
- 3 If tub is 700 series then move to Pump 2 and perform same procedure as in step 2.
- 4 Remove the assembly that runs from the hush pump to the heater and blow into the heater pipe to clear water from circulate on system. If your LEEP model has a hush pump, remove the assembly from the hush pump to the heater.
- 5 If your hot tub has a ClearTech UVC System, undo the union on the end furthest from the hot tub to allow water inside to drain out.
- 6 Now, switch the ShopVac to suck and stick the hose on to the top of each pump and suck water out of the pump wet ends.
- 7 Suck all of the water out of the hot tub and floor drain. Leave your drain valve in open position and attach valve assemblies back onto the pumps making sure gaskets are in place. Leave hush pump to heater assembly off at the heater to allow air into the heater pipe over the winter.
- 8 Secure and cover your hot tub cover with a tarp.

